

**PS**

Paddle system



**ICETECH**  
ICE MAKERS



## Paddle system



PS 22



PS 22 PLUS



PS 32



PS 42



PS 52



PS 62



PS 82



PS 122

## General features

Just ideal! The best cube our drink and our ice machine can get!

Large volume and finger sized cubes for efficient cooling with maximum heat transfer in the hottest of ambient temperatures.

**ICE TECH PS** is fully electromechanical controlled without injectors or pump, which makes it extremely reliable in the toughest water conditions.

The high grade food safe stainless steel and superior density insulation will ensure quality with optimized energy consumption.

## Technical features / Operating limits

Ice Cube	20gr. adjustable soft & long lasting.
Body	AISI 304 Stainless Steel.
Paddle system	The <b>ICE TECH PS</b> machine are unaffected by limescale or bad water quality. No pump and no spray.
Electromechanical control	Simple, easy to understand and service. High reliability and low spare parts cost.
Switch	External On/Off switch.
Tropicalized machines	Class T
Operating conditions	Air temperature: 10 – 43°C Water temperature: 5 – 38°C Water pressure: 0,7 – 6 bar
Ice Production capacity	Kg/24h at Ambient temperature 21°C, Water temperature 15°C.
Certification	ISO 9001, CE
Others	Refrigerant R452A & R290 Water inlet connection Ø=3/4" Gas Drain connection Ø=20 mm Single-phase input 220V-50Hz. / Optional: 220V-60Hz



Model	Condensation System	Production Kg. / Day	Storage Kg.	Maximum Power Input W.	 <b>WIDTH x DEPTH x HEIGHT</b> Dimensions mm.
ICE TECH PS 22 R290	Air	22	6	287	401 x 506 x 643*
	Water	24			
ICE TECH PS 22 PLUS R290	Air	22	12	287	401 x 506 x 698*
	Water	24			
ICE TECH PS 32 R290	Air	31	12	293	401 x 506 x 698*
	Water	33			
ICE TECH PS 42 R290	Air	38	12	421	401 x 506 x 698*
	Water	40			
ICE TECH PS 52	Air	48	25	550	513 x 557 x 811**
	Water	51			
ICE TECH PS 62	Air	55	30	650	593 x 557 x 934**
	Water	60			
ICE TECH PS 82	Air	75	37	775	673 x 557 x 984**
	Water	81			
ICE TECH PS 122	Air	122	50	800	843 x 557 x 984**
	Water	130			

\* Legs + 12 - 20 mm  
 \*\* Legs + 105 - 155 mm